



SAFETY DATA SHEET FLAM SPRAY DUSTER 400ml

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME FLAM SPRAY DUSTER 400ml
PRODUCT NO. AWSDU400F_PL
SUPPLIER AF INTERNATIONAL. A division
of HK WENTWORTH LTD
KINGSBURY PARK.
MIDLAND ROAD,
SWADLINCOTE
DERBYSHIRE DE11 0AN
UNITED KINGDOM
+44 (0) 1283 222111
+44 (0) 1283 550177
info@hkw.co.uk

2 HAZARDS IDENTIFICATION

Extremely flammable
CLASSIFICATION (1999/45) F+;R12.

3 COMPOSITION/INFORMATION ON INGREDIENTS

| Name | EC No. | CAS-No. | Content | Classification (67/548) |
|---------|-----------|----------|---------|-------------------------|
| PROPANE | 200-827-9 | 74-98-6 | 60-80% | F+;R12 |
| BUTANE | 203-448-7 | 106-97-8 | 10-30% | F+;R12 |

The Full Text for all R-Phrases are Displayed in Section 16

COMPOSITION COMMENTS

Ingredients not listed are classified as non-hazardous or at a concentration below reportable levels

4 FIRST-AID MEASURES

INHALATION

Move the exposed person to fresh air at once. Provide rest, warmth and fresh air.

INGESTION

Not relevant.

SKIN CONTACT

Wash the skin immediately with soap and water. Get medical attention if any discomfort continues.

EYE CONTACT

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

5 FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA

Use: Powder. Dry chemicals, sand, dolomite etc. Water spray, fog or mist.

SPECIAL FIRE FIGHTING PROCEDURES

Containers close to fire should be removed or cooled with water. Use water to keep fire exposed containers cool and disperse vapours.

UNUSUAL FIRE & EXPLOSION HAZARDS

Aerosol cans may explode in a fire.

6 ACCIDENTAL RELEASE MEASURES

FLAM SPRAY DUSTER 400ml

SPILL CLEAN UP METHODS

Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate.

7 HANDLING AND STORAGE

USAGE PRECAUTIONS

Keep away from heat, sparks and open flame. Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level.

STORAGE PRECAUTIONS

Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

| Name | Std | TWA - 8 hrs | | STEL - 15 min | | Notes |
|--------|-----|-------------|------------|---------------|------------|-------|
| BUTANE | WEL | 600 ppm | 1450 mg/m3 | 750 ppm | 1810 mg/m3 | |

WEL = Workplace Exposure Limit.

INGREDIENT COMMENTS

WEL = Workplace Exposure Limits

ENGINEERING MEASURES

All handling to take place in well-ventilated area.

RESPIRATORY EQUIPMENT

No specific recommendation made, but respiratory protection must be used if the general level exceeds the recommended occupational exposure limit.

HAND PROTECTION

Use suitable protective gloves if risk of skin contact. The most suitable glove must be chosen in consultation with the gloves supplier, who can inform about the breakthrough time of the glove material.

EYE PROTECTION

Wear approved, tight fitting safety glasses where splashing is probable.

OTHER PROTECTION

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

HYGIENE MEASURES

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. When using do not eat, drink or smoke.

9 PHYSICAL AND CHEMICAL PROPERTIES

| | | | |
|-------------------------------|----------------------|--------------------------------|---------|
| APPEARANCE | Aerosol Liquid | | |
| COLOUR | Colourless | | |
| ODOUR | Characteristic | | |
| SOLUBILITY | Insoluble in water | | |
| FLASH POINT (°C) | -40 CC (Closed cup). | AUTO IGNITION TEMPERATURE (°C) | 410/580 |
| FLAMMABILITY LIMIT - LOWER(%) | 1.8 | FLAMMABILITY LIMIT - UPPER(%) | 10 |

10 STABILITY AND REACTIVITY

STABILITY

Stable under normal temperature conditions.

CONDITIONS TO AVOID

Avoid heat, flames and other sources of ignition. Avoid contact with: Strong oxidising agents. Strong alkalis. Strong mineral acids.

HAZARDOUS DECOMPOSITION PRODUCTS

Fire creates: Vapours/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO₂).

11 TOXICOLOGICAL INFORMATION

GENERAL INFORMATION

No specific health warnings noted.

FLAM SPRAY DUSTER 400ml

12 ECOLOGICAL INFORMATION

ECOTOXICITY

Not regarded as dangerous for the environment.

13 DISPOSAL CONSIDERATIONS

DISPOSAL METHODS

Empty containers must not be burned because of explosion hazard. Dispose of waste and residues in accordance with local authority requirements.

14 TRANSPORT INFORMATION



| | | | |
|----------------------|----------------|------------------|-----------------------------|
| UK ROAD CLASS | 2.1 | | |
| PROPER SHIPPING NAME | AEROSOLS | | |
| UN NO. ROAD | 1950 | UK ROAD PACK GR. | Not Applicable |
| ADR CLASS NO. | 2.1 | ADR CLASS | Class 2.1: Flammable gases. |
| ADR PACK GROUP | Not Applicable | ADR LABEL NO. | 2.1 |
| CEFIC TEC(R) NO. | 20G5F | RID CLASS NO. | 2.1 |
| RID PACK GROUP | Not Applicable | UN NO. SEA | 1950 |
| IMDG CLASS | 2.1 | IMDG PACK GR. | Not Applicable |
| EMS | F-D; S-U | MFAG | See Guide |
| MARINE POLLUTANT | No. | UN NO. AIR | 1950 |
| AIR CLASS | 2.1 | AIR PACK GR. | Not Applicable |

15 REGULATORY INFORMATION

SYMBOLS



Extremely Flammable

RISK PHRASES

R12 Extremely flammable.

SAFETY PHRASES

S9 Keep container in a well-ventilated place.
S16 Keep away from sources of ignition - No smoking.
S51 Use only in well-ventilated areas.
A1 Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.
A2 Do not spray on a naked flame or any incandescent material.
S2 Keep out of the reach of children.

UK REGULATORY REFERENCES

Chemicals (Hazard Information & Packaging) Regulations.

The Control of Substances Hazardous to Health Regulations 2002 (S.I 2002 No. 2677) with amendments.

ENVIRONMENTAL LISTING

Control of Pollution Act 1974. Control of Pollution (Special Waste Regulations) Act 1980. Rivers (Prevention of Pollution) Act 1961.

EU DIRECTIVES

Dangerous Substance Directive 67/548/EEC.

FLAM SPRAY DUSTER 400ml

Dangerous Preparations Directive 1999/45/EC.

System of specific information relating to Dangerous Preparations. 2001/58/EC.

Commission Directive 2000/39/EC of 8 June 2000 establishing a first list of indicative occupational exposure limit values in implementation of Council Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work.

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments.

APPROVED CODE OF PRACTICE

Classification and Labelling of Substances and Preparations Dangerous for Supply. Safety Data Sheets for Substances and Preparations.

GUIDANCE NOTES

Workplace Exposure Limits EH40.

16 OTHER INFORMATION

REVISION COMMENTS

Revised in accordance with CHIP3 and EU Directives 1999/45/EC and 2001/58/EC

ISSUED BY

Pawel Zmarzly

REVISION DATE AUGUST 2010

REV. NO./REPL. SDS 0

GENERATED

SDS NO. 13100

RISK PHRASES IN FULL

R12 Extremely flammable.

DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.